

Sealed. Power.



When the Power Goes Off, We Power the World's Critical UPS Applications: Embassy

When you need a dependable, rechargeable, sealed maintenance-free battery for critical VRLA applications...you need the battery that the world turns to: Embassy. Powerful. Reliable. Providing a long service life in crucial applications.

**UPS & Power Management Systems • Electric Vehicles • Medical & Mobility Applications
Railroad Systems • Off-Grid Power Networks • Telecommunication Installations**



The advanced technology that drives Embassy VRLA batteries is the technology that provides the power demands of people throughout the world. Power that makes life easier. Power that helps raise the standard of living, health and safety for many communities. Embassy...the perfect power solution.



SPECIFICATIONS

Model Number	BCI Group	Voltage	20 Hr Ah	Product Footnote	Physical Specifications										
					Inches			Millimeters			Term. Height		Weight		Package Quantity
					L	W	H	L	W	H	in.	mm.	lbs.	kgs.	
Embassy® AGM Series															
4CE4.5		4	4.5	T1	1.89	1.89	4.02	48	48	102	4.25	108	1.07	0.49	20
4CE10		4	10.0	T1	4.02	1.73	3.74	102	44	95	3.98	101	2.28	1.04	10
6CE1.2		6	1.2	T1	3.82	0.94	2.05	97	24	52	2.28	58	0.64	0.29	40
6CE3		6	3.0	T1	5.28	1.38	2.40	134	35	61	2.64	67	1.46	0.66	20
6CE5		6	5.0	T1	2.76	1.85	3.98	70	47	101	4.21	107	1.58	0.72	20
6CE7.5		6	7.5	T1	5.94	1.34	3.70	151	34	94	3.94	100	2.52	1.15	10
6CE8		6	8.0	T1	3.86	2.20	4.61	98	56	117	4.69	119	2.86	1.30	10
6CE12		6	12.0	T1, T2	5.94	1.97	3.70	151	50	94	3.94	100	4.18	1.90	10
6CE14		6	14.0	T3,TS,TH,CQ	4.25	2.80	5.51	108	71	140	5.51	140	5.16	2.34	10
6CE36		6	36.0	T2,B1	6.38	3.46	6.41	162	88	163	6.69	170	12.62	5.73	4
6CE220	6V-27	6	220.0	M6	12.09	6.65	8.85	307	169	220	8.85	220	63.23	28.68	1
12CE1.2		12	1.2	T1	3.82	1.69	2.05	97	43	52	2.28	58	1.20	0.55	20
12CE2.3		12	2.3	T1	7.01	1.38	2.40	178	35	61	2.64	67	2.12	0.96	10
12CE3		12	3.0	T1	5.28	2.64	2.40	134	67	61	2.64	67	2.84	1.29	10
12CE5		12	5.0	T1	3.54	2.76	3.98	90	70	101	4.21	107	3.73	1.69	10
12CE7.5		12	7.5	T1,T2	5.94	2.56	3.70	151	65	94	3.94	100	4.80	2.18	8
12CE10	Scooter	12	10.0	T2	5.95	2.56	4.37	151	65	111	4.60	117	6.38	2.90	8
12CE12		12	12.0	T1,T2	5.94	3.86	3.74	151	98	95	3.98	101	8.00	3.63	4
12CE18		12	18.0	B1,T2	7.13	3.03	6.57	181	77	167	6.57	167	11.61	5.27	2
12CE21		12	21.0	M5	7.13	3.03	6.57	181	77	167	6.57	167	13.90	6.30	2
12CE21 W/C	UPS	12	21 Wattspercell	Recess	3.54	2.76	3.98	90	70	101	3.98	101	3.97	1.90	10
12CE26		12	26.0	B1,T2	6.50	6.93	5.00	165	176	127	5.00	127	17.14	7.78	1
12CE35	U1	12	35.0	J,H	7.68	5.12	6.10	195	130	155	7.09	180	22.33	10.13	1
12CE40		12	40.0	B2	7.76	6.50	6.73	198	165	171	6.73	171	28.57	12.96	1
12CE55	22NF	12	55.0	J	9.02	5.43	8.19	229	138	208	9.06	230	36.74	16.67	1
12CE75	24	12	75.0	J,M,H	10.20	6.61	8.31	260	168	211	9.06	230	49.26	22.35	1
12CE100	27	12	100.0	J,M,H	12.09	6.65	8.31	307	169	211	9.17	233	59.99	25.85	1
Embassy® Gel Series															
6CEG225	GC2	6	225.0	Std	10.25	7.13	10.50	260	181	275	10.75	273	60.78	27.57	1
12CEG33	U1	12	33.0	J	7.71	5.18	6.18	196	132	157	7.19	183	26.17	11.87	1
12CEG55	22NF	12	55.0	J	9.00	5.43	8.31	229	138	211	9.50	241	42.36	19.22	1
12CEG75	24	12	75.0	Std	10.20	6.57	8.20	259	167	208	9.37	238	59.81	27.13	1
12CEG100	27	12	98.0	Std	12.00	6.57	8.20	305	167	208	9.37	238	68.33	31.00	1
12CEG110	31	12	110.0	S	13.50	6.76	8.50	343	172	216	9.31	236	82.00	37.20	1
12CEG135	920	12	135.0	M8	13.50	6.76	10.70	343	172	271	10.91	277	104.79	47.53	1
12CEG200	4D	12	200.0	A	21.00	8.50	8.88	533	216	226	10.00	254	118.00	53.52	1
12CEG225	4D	12	225.0	A	21.00	8.50	8.88	533	216	226	10.00	254	160.94	73.20	1
Embassy® AGM Monobloc Series															
CE704	0809-0010	4	5.0	T2	3.81	2.13	3.02	97	54	77			1.46	0.66	16
CE705	0859-0010	4	8.0	T2	3.81	2.13	4.00	97	54	102			2.02	0.92	16
CE706	0809-0012	6	5.0	T2	5.48	2.13	3.02	139	54	77			2.16	0.98	16
CE707	0859-0012	6	8.0	T2	5.48	2.13	4.00	139	54	102			3.15	1.43	16
CE708	0818-0012	6	2.5	T1	4.48	1.81	2.75	114	46	70			1.15	0.52	16

Product Footnote			
A	SAE "Automotive" Type Terminal	M8	Inserted M8 Threaded Bolt Terminal
B1	Nut & Bolt M5	Recess	Recessed Positive T2, Recessed Negative T1
B2	Nut & Bolt M6	S	0.250 in. Stainless Threaded Terminal
CQ	Fused Wire Leads with CQ Type Connector	Std	Dual SAE/Stainless Threaded Terminal
H	Fitted with Handle	T1	Quick Disconnect Tabs 0.187 in x 0.032 in
J	Heavy Duty Nut & Bolt	T2	Quick Disconnect Tabs 0.250 in x 0.032 in
M	Marine Combination Terminal	T3	Polarized Quick Disconnect Tabs
M5	Inserted M5 Threaded Bolt Terminal	TH	Fused Wire Leads with H Type Connector
M6	Inserted M6 Threaded Bolt Terminal	TS	Fused Wire Leads with S Type Connector



1445 Majestic Drive
P.O. Box 990
Fremont, OH 43420-0990 USA
419-334-7181
Fax 419-334-7124
www.crownbattery.com
sales@crownbattery.com

Specifications are subject to change without notice.